

# XS WIRELESS 2 HEADMIC SET

XSW 2-ME3



## DESCRIPTION

Hands-free performance. High flexibility for those willing to go a step further. XS WIRELESS 2 grows with your demands by offering an intuitive LCD display for more manual options and 12 compatible channels in a stable UHF band, withstanding tougher live stage conditions.

The XS WIRELESS 2 HEADMIC SET is an easy to use all-in-one wireless system for singers and performers, excellent for live sound that involves dancing and singing all at the same time. Metal receiver housing and rackmount kit included.



## SCOPE OF SUPPLY

- 1 receiver EM-XSW 2
- 1 bodypack transmitter SK-XSW
- 1 headmic ME 3-II, incl. windshield
- 1 power supply NT 12-5 CW
- 2 AA batteries
- 1 rackmount kit
- 1 pouch
- user manual

## FEATURES

- Lightweight headmic for hands-free operation and compact bodypack transmitter
- True diversity receiver with metal housing
- External antennas
- Automatic frequency management and synchronization via remote channel for easy setup
- Fully tunable over a wide range of UHF frequencies
- Rackmount kit included
- Up to 12 compatible channels

## ACCESSORIES / SPAREPARTS

- NT 12-5 CW power supply unit
- ME 3-II headset microphone

*For more accessories and spareparts please visit [www.sennheiser.com](http://www.sennheiser.com)*

## PRODUCT VARIANTS

■ 507129	XSW 2-ME3-A	A-Range: 548 - 572 MHz	incl. ME 3-II condenser, cardioid microphone
■ 507130	XSW 2-ME3-B	B-Range: 614 - 638 MHz	incl. ME 3-II condenser, cardioid microphone
■ 507131	XSW 2-ME3-C	C-Range: 766 - 790 MHz	incl. ME 3-II condenser, cardioid microphone
■ 507132	XSW 2-ME3-D	D-Range: 794 - 806 MHz	incl. ME 3-II condenser, cardioid microphone
■ 507133	XSW 2-ME3-E	E-Range: 821 - 832 MHz, 863 - 865 MHz	incl. ME 3-II condenser, cardioid microphone
■ 507134	XSW 2-ME3-GB	GB-Range: 606 - 630 MHz	incl. ME 3-II condenser, cardioid microphone
■ 507135	XSW 2-ME3-K	K-Range: 925 - 937,5 MHz	incl. ME 3-II condenser, cardioid microphone

## PACKAGING

Master carton 3 pcs.

507129 XSW 2-ME3-A EAN: 4044155213935, UPC: 615104279513 / 507130 XSW 2-ME3-B EAN: 4044155213942, UPC: 615104279520  
507131 XSW 2-ME3-C EAN: 4044155213959, UPC: 615104279612 / 507132 XSW 2-ME3-D EAN: 4044155213966, UPC: 615104279636  
507133 XSW 2-ME3-E EAN: 4044155213973, UPC: 615104279704 / 507134 XSW 2-ME3-GB EAN: 4044155213980, UPC: 615104279711  
507135 XSW 2-ME3-K EAN: 4044155213997, UPC: 615104279735

**SENNHEISER**

# XS WIRELESS 2 HEADMIC SET

XS W 2-ME3



## TECHNICAL DATA

### SYSTEM (XS W 2-ME3)

Modulation .....	wideband FM
Frequency ranges .....	A: 548-572 MHz, GB: 606-630 MHz B: 614-638 MHz, C: 766-790 MHz D: 794-806 MHz, E: 821-832 MHz, 863-865 MHz K: 925-937.5 MHz
Switching bandwidth .....	up to 24 MHz
Frequencies .....	8 frequency banks, each with up to 12 factory-preset channels
Signal-to-noise ratio .....	≥ 103 dBA
THD .....	≤ 0.9%
Temperature range .....	operation: 0°C to +40°C storage: -20°C to +70°C
Transmitter synchronization.....	2.4 GHz, Low Power OQPSK (only active during synchronization)

### RECEIVER (EM-XSW 2)

Receiver principle .....	double superheterodyne
Diversity principle .....	True Diversity
Sensitivity (at peak deviation) .....	< 3 µV at 52 dB(A)rms S/N
AF frequency response .....	50 to 16,000 Hz (-3 dB)
Max. AF output voltage (at peak deviation, 1 kHz AF) .....	1/4" (6.3 mm) jack socket (unbalanced): +6 dBu, XLR socket (balanced): +12 dBu
Audio adjustment range .....	40 dB, adjustable in 5-dB steps
Power supply .....	12 V DC nom. / 300 mA
Squelch .....	adjustable from 3 dBµV to 28 dBµV (combined with pilot tone)
Line/Mic level .....	20 dB, switchable
Housing material .....	rugged metal housing
Dimensions (W x H x D) .....	approx. 200 x 42 x 127 mm
Weight .....	approx. 680 g

### BODYPACK TRANSMITTER (SK-XSW)

RF output power .....	10 mW
AF frequency response.....	Line: 50-16,000 Hz Mic: 50-16,000 Hz
Audio Input .....	3.5 mm jack socket
Max. input voltage (Mic/Line) at 3% THD.....	typ. 1.V rms Mic / typ. 2.6 V rms Line at -30 dB gain
Power supply .....	2 AA size batteries, 1.5 V
Operating time .....	approx. 10 hrs
Adjustment range of transmitter sensitivity.....	0 to -30 dB, adjustable in 10 dB steps
Housing material .....	rugged ABS housing
Dimensions (W x H x D) .....	approx. 71 x 96 x 28 mm
Weight.....	approx. 95 g

### HEADSET MICROPHONE (ME 3-II)

Transducer principle .....	condenser, pre-polarized
Sensitivity .....	1.6 mV/Pa
Pick-up pattern.....	cardioid
Max. SPL.....	150 dB

## CONNECTIONS

### RECEIVER



## AVAILABLE SETS XS WIRELESS 2

- XS W 2 VOCAL SETS
  - e835 (superior dynamic, cardioid) or
  - e865 (condenser, super-cardioid)
- XS W 2 INSTRUMENT SET
- XS W 2 HEADMIC SET
- XS W 2 LAVALIER MIC SET

## ALSO AVAILABLE XS WIRELESS 1

Get started. Go for XS WIRELESS 1 and rely on a solid wireless transmission with up to 10 compatible channels in a stable UHF band.

- XS W 1 VOCAL SETS
  - e825 (dynamic, cardioid) or e835  
(superior dynamic, cardioid)
- XS W 1 INSTRUMENT SET
- XS W 1 HEADMIC SET
- XS W 1 LAVALIER MIC SET
- XS W 1 BRASS SET